


YXR1004

D RING WITH STRAP, TYPE A

ITEM NO.	SIZE (IN.)	MBS (LBS.)	WEIGHT (LBS.)	DIMENSIONS (MM)						
				A	B	C	D	E	F	G
YXR1004-01	3/8	3000	0.81	51	68	9.5	51	20	6	15
YXR1004-02	1/2	12000	0.94	63.5	57.1	13	45	25	8	33
YXR1004-03	5/8	18000	1.87	75	75	16	63.5	31	9.5	37
YXR1004-04	3/4	26500	2.70	75	75	19	63.5	35	9.5	40
YXR1004-05	1	47000	4.21	75	75	25	63.5	41	9.5	63
YXR1004-06	1	47000	4.74	100	75	25	63.5	41	9.5	63

◆ Ultimate Load at 4 Times the Working Load Limit.




YXR1005

D RING WITH STRAP, TYPE B

ITEM NO.	SIZE	WLL (T)	PL (T)	MBS (T)	WEIGHT (LBS.)	DIMENSIONS (MM)								
						L	L1 (±1)	L2	H1 (±1)	H2	H	B	W	A
YXR1005-01	20T	5	7.5	20	2.21	90	120	170	70	102	30	10	42	16
YXR1005-02	36T	9	13.5	36	5.42	120	136	212	80	122	35	10	42	21
YXR1005-03	41T	10.5	15.4	41	8.15	125	144	225	88	138	43	12	62	25
YXR1005-04	50T	18.75	18.75	50	9.71	130	151	241	90	144	48	14	65	27

◆ Ultimate Load at 4 Times the Working Load Limit.




YXR1006

D RING WITH STRAP, TYPE C

ITEM NO.	SIZE	MBS (T)	WEIGHT (KG)	DIMENSIONS (MM)											
				A	A1	B	B1	D	F	C	E	K	G	H	L
YXR1006-01	MBS7T	7	0.5370	65.5	123.1	51.1	76.1	12.7	12.3	50	16.2	5.9	32.2	42	12.5
YXR1006-02	MBS36T	36	2.5330	121	191.4	81	128.4	23.8	23.8	102	27	11.3	48.12	67	22.5
YXR1006-03	MBS41T	41	3.4040	126.5	202	92.8	144	25.9	25.3	102	31.8	13.5	63	82.5	25
YXR1006-04	MBS50T	50	4.1190	127	223	102	155	27.2	26.5	102	31	13.5	63	83	26.5

◆ Ultimate Load at 4 Times the Working Load Limit.



YXR1007

D RING WITH STRAP, TYPE B

ITEM NO.	SIZE	DIMENSIONS (MM)								
		H	H1	L	L1	L2	A	K	T	C
YXR1007-01	20T	87	50	137	90	80	42	18	24	10
YXR1007-02	25T	109	69	170	112	90	48	20	25	10
YXR1007-03	30T	102	58	144	88	80	42	21	24	10
YXR1007-04	36T	112	66.5	165	100	90	50	24	35	12
YXR1007-05	36T	124	76	208	130	120	45	23	30	12
YXR1007-06	41T	137	87	225	143	120	50	26	48	12
YXR1007-07	50T	140	86	227	137	120	50	27	48	12

◆ Ultimate Load at 4 Times the Working Load Limit.